

- 8.5 X 50 Aluminum Renegade Gooseneck Trailer
- Electrical Package 3
- Floor Mounted E-Track (3 runs at 42')
- Wall Mounted E-Track (2 runs at 50')
- 5 Foot Extended Ramp Flap
- Diamond Plate Ramp Door
- Diamond Plate Transition Flap
- 5 Inch Rubber Ramp Door Bumpers X 4
- Generator Door, Vented (36" X 24")
- Generator Slide Out
- 8,000 Pound Warn Winch
- 18' Awning (9000 Series With Metal Weather Shield) X 2
- White Vinyl Ceiling
- 96" Base Cabinet, 3 Door, 96h X 40h X 20d (C-Tech)
- Diamond Plate 5' Flap
- Upgrade To .040 Epoxy Sides

NOTE: Cabinets against front wall

**NOTE:** Breaker box and battery above cabinets

NOTE: Halogens 3' in under both awnings

NOTE: 110 volt receptacles—1 by back door, 1 above cabinets

**NOTE:** GFI left side of side door **NOTE:** Wall switch by side door

**NOTE:** Fluorescents staggered evenly

**NOTE:** Winch to be placed at manufacturers recommendation

NOTE: Awnings to start at back passenger side run side by side as

close together as possible (not to cover side door)