



- 8.5 X 28 Enclosed Trailer
- All Standard Equipment As Listed On Website
- Fold Down Stabilizer Jacks X 2 Sets (All 4 Corners)
- 24 Inches Additional Interior Height
- V-Nose
- Door Hold Back Latch X 2 (Both Doors)
- Upgrade To Chrome Rims / Radial Tires
- Spare Radial Tire
- Inside Spare Tire Mount
- Entry Assist Handle (Aluminum Grab Handle) X 2
- 32 Inch Aluminum Slide Out Step (For 36 Inch Side Door)
- 48 Inch Aluminum Slide Out Step (For 48 Inch Rear Door)
- Wire And Brace For A/C
- 13.5K BTU A/C Unit With Heat Strip
- 4 Foot Baseboard Heater X 2
- Fan-Tastic Power Roof Vent With Thermostat (12V)
- Comfort Control / Analog Dual A/C Thermostat (For Multiple Units)
- Black In Color
- 25' LX Awning (Elite 9000) With Center Support (Black or Gray)
- Ceiling Liner
- Wall Insulation
- Ceiling Insulation
- Extra 110V Interior Receptacle X 4
- Extra 4 Foot Fluorescent Light X 2
- Motor Base Plug
- Exterior 500W Recessed Quartz Light X 2
- LED Tail Lights
- Electrical Package

NOTE #1 – No ramp door. Customer wants a SINGLE 48 inch rear door centered in rear

NOTE #2 – If possible, customer wants height stenciled on top right and left of trailer.

NOTE #3 – Spare tire mount to be placed low and inside V-Nose

NOTE #4 – Exterior quartz lights mounted on either side of awning.

NOTE #5 – Place electric vent in front ½ of trailer. Non-powered vent in rear ½ of trailer.

NOTE #6 – Mount 2 fluorescent lights in front half of trailer and 2 in rear half.

NOTE #7 – Place 3 receptacles in front half and 3 in rear half of trailer.